



Shenzhen Bvsion Technology Co., Ltd.

Tel: 0086 755 23059953 Mobile: 0086-13924666965 / 00852-9373 7704 Contact: Gina Yu

E-Mail: bvs.gina@lclbvs.com Website: <http://www.lclbvs.com> / <http://www.bvsipe.com>

Office Address: 5F, Building 9, Huafeng Science Park, Fengtang Avenue, Tangwei Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China, 518102.

Product Parameters

Photo			
Item	Specification		
Model	BVS-808		
Print Method	Direct Thermal		
Resolution	576 dots/line		
Printing Width	80mm (max) / 72mm (default)		
Paper Separator (Option)	48mm 52mm 56mm 64mm 68mm 76mm 80mm		
Input Buffer	256K bytes		
NV Flash	256K bytes		
Interface	U /U+S /U+L/ U+S+L/ U+BT /U+W/ U+S+L+BT / U+S+L+W		
Print Speed	200-260mm/s		
Font A	12×24		
Font B	9×17		
Chinese	GB18030, BIG5 24×24 dots		
Japanese/Korean	Optional		
User-defined Characters	Supported		
1D Barcode	UPC-A/UPC-E /JAN13(EAN13)/ JAN8(EAN8)/ CODE39 /ITF /CODABAR /CODE93/ CODE128		
2D Barcode	QR Code		
Sensors	Paper shortage, cover open, overheat, cutter stuck		
Power Supply	AC 100V-240V 50/60Hz, DC 24V/2.5A		
Paper Type	Thermal Receipt Paper		
Paper Width	Max. 79.5±0.5mm		
Paper Thickness	0.06~0.08mm		
Roll Diameter	Max. Ø80mm		
Paper Loading	Easy paper loading		
Paper Cutting	Auto-cutter		
Operating Environment	0°C~45°C, 10%~80%RH		
Storage Environment	-10°C~60°C, 10%~90%RH		
Dimensions	185(D)×145(W)×134(H) mm		
Net Weight / Gross Weight	Net: 1.2kg / Gross: 1.85kg		
Print Head Life	100KM		
Cutter Life	1.0 million cuts		
Accessories	Data cable, Power adaptor, Power cord, Paper roll, CD, Manual, Roller, Paper separator (optional)		
Individual Box Size	266×164×160mm (L×W×H), 1 unit/carton		
Master Carton Size	575×370×535mm (L×W×H), 12 units/carton		
Emulation / Driver	ESC/POS, Windows/Linux/Mac		
SDK	Android iOS Windows		