



## Shenzhen BvSION Technology Co., Ltd.

Tel: 0086 755 23059953 Mobile: 0086-13924666965 / 00852-9373 7704 WhatsApp: +852 93737704

E-Mail: bvs.gina@lcbv.com Website: http:// www.lcbv.com / http:// www.bvsipc.com

Office Address: 5F, Building 9, Huaifeng Science Park, Fengtang Avenue, Tangwei Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China, 518102.

### Specification document

|              |                  |          |                                                                   |
|--------------|------------------|----------|-------------------------------------------------------------------|
| Model NO.    | BVS-QW104-J1900  | Standard | 10.4", Intel Celeron J1900, 8+128GB, win 10 64 bit trial version. |
| Brand name   | BVS/OEM          |          |                                                                   |
| Product Type | Windows Panel PC |          |                                                                   |
| Date         | 2026/8/3         |          |                                                                   |



|             |                                        | Standard                                  | optional                          |
|-------------|----------------------------------------|-------------------------------------------|-----------------------------------|
| System      | CPU                                    | Intel Celeron J1900                       | Intel Celeron J4125 / J6412       |
|             | Frequency                              | 2.0GHZ                                    | /                                 |
|             | RAM                                    | 8GB                                       | 4GB / 8GB                         |
|             | SSD                                    | 128GB                                     | 64GB / 128GB / 256GB / 512GB      |
|             | Operating system                       | Win10                                     | Windows 7 / 8 / 11 / Linux / Unix |
| Display     | Screen                                 | Industrial LCD Screen                     | /                                 |
|             | Resolution                             | 1024 (RGB) × 768, WXGA                    | /                                 |
|             | Viewing angle                          | 20/30/45/45 (Typ.) (CR≥10)                | /                                 |
|             | Contrast ratio                         | 800:1                                     | /                                 |
|             | Brightness                             | 250 cd/m <sup>2</sup> (Typ.)              | 400/500 cd/m <sup>2</sup> (Typ.)  |
| Network     | Screen scale                           | /                                         | /                                 |
|             | Wi-Fi                                  | 2.4G Wi-Fi, 802.11b/g/n                   | /                                 |
|             | Ethernet                               | Gigabit network port                      | /                                 |
|             | BT                                     | /                                         | Bluetooth                         |
|             | USB                                    | USB 2.0 * 2, USB 3.0 * 2                  | /                                 |
| Interfaces  | COM                                    | RS232*2                                   | Customizable                      |
|             | HD                                     | 1                                         | /                                 |
|             | VGA                                    | 1                                         | /                                 |
|             | LAN                                    | 1                                         | /                                 |
|             | DC-IN                                  | 1                                         | /                                 |
| Multi-Media | Audio                                  | Built-in Speaker * 1                      | /                                 |
| Accessories | Adapter                                | AC 100-240V 50/60Hz, DC 12V/5A (DC 2.5mm) | /                                 |
| Temperature | Working temperature                    | 10°C ~ 70°C                               | /                                 |
|             | Storage temperature                    | -20°C ~ 70°C                              | /                                 |
| Mounting    | VESA Mount                             | /                                         | Customizable                      |
|             | Panel Mount                            | /                                         | Customizable                      |
|             | Stand Mount                            | /                                         | Customizable                      |
| Packaging   | Net weight                             | 1.7kg                                     | /                                 |
|             | Gross weight                           | 2.4 kg                                    | /                                 |
|             | Product dimensions                     | 208*261*46mm (L*W*H)                      | /                                 |
|             | Single Unit Package Dimension          | 490*340*130mm (L*W*H)                     | /                                 |
|             | Carton Dimension                       | 500*520*340mm (L*W*H) (Ctn Qty:5 pcs)     | /                                 |
| OEM         | Appearance, Interface, CPU, Logo, etc. |                                           |                                   |

The specifications provided in this document represent the standard configuration. For customized solutions or more detailed technical information, please do not hesitate to contact us.