



## Shenzhen Bvsion Technology Co., Ltd.

Tel: 0086 755 23059953 Mobile: 0086-13924666965 / 00852-9373 7704 WhatsApp: +852 93737704

E-Mail: bvs.gina@lcdbvs.com Website: <http://www.lcdbvs.com> / <http://www.bvsipc.com>

Office Address: 5F ,Building 9, Huaifeng Science Park, Fengtang Avenue, Tangwei Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China, 518102.

### Specification document

|              |                   |          |                                  |
|--------------|-------------------|----------|----------------------------------|
| Model NO.    | BVS-VR156         | Standard | 15.6", RK3588, 8+128GB, Android. |
| Brand name   | BVS\OEM           |          |                                  |
| Product Type | Android Tablet PC |          |                                  |
| Date         | 2026/7/20         |          |                                  |



|                 |                                        | Standard                                                         | optional                           |
|-----------------|----------------------------------------|------------------------------------------------------------------|------------------------------------|
| System          | CPU                                    | Rockchip RK3588                                                  | RK3288/RK3399/RK3566/RK3568/RK3576 |
|                 | Frequency                              | UP to 2.4GHz                                                     | /                                  |
|                 | GPU                                    | Mali-G610 MC4                                                    | /                                  |
|                 | NPU                                    | 6.0 TOPS                                                         | /                                  |
|                 | RAM                                    | 8GB                                                              | 2GB/4GB                            |
|                 | EMMC                                   | 128GB                                                            | 32GB/64GB                          |
|                 | Operating system                       | Android 12                                                       | /                                  |
| Display         | Screen                                 | 15.6-inch touch screen display                                   | 15.6-inch non-touch display        |
|                 | Resolution                             | 1920*1080                                                        | /                                  |
|                 | Viewing angle                          | 89/89/89/89 (Typ.)(CR≥10)                                        | /                                  |
|                 | Contrast ratio                         | 800: 1                                                           | /                                  |
|                 | Brightness                             | 250 cd/m <sup>2</sup>                                            | 500 cd/m <sup>2</sup>              |
|                 | Screen scale                           | 16:9                                                             | /                                  |
| Network         | Wi-Fi                                  | 2.4G+5G-Wi-Fi, supporting Wi-Fi 802.11b/g/n protocols            | /                                  |
|                 | Ethernet                               | Gigabit network port                                             | /                                  |
|                 | BT                                     | Bluetooth 5.0                                                    | /                                  |
|                 | 4G LTE                                 | NO                                                               | Customizable                       |
|                 | USB                                    | 2                                                                | /                                  |
| Interfaces      | COM                                    | /                                                                | RS232/RS485                        |
|                 | HD                                     | /                                                                | /                                  |
|                 | TF card slot                           | 1                                                                | /                                  |
|                 | LAN                                    | 1                                                                | /                                  |
|                 | SIM-4G                                 | /                                                                | 1                                  |
|                 | DC-IN                                  | 1                                                                | /                                  |
|                 | Video                                  | MPEG-1,MPEG-2,MPEG-4,H.263,H.264,VC1,RV etc.,support up to 1080p | /                                  |
| Multi-Media     | Audio                                  | MP3/WMA/AAC etc.                                                 | /                                  |
|                 | Picture                                | jpeg, jpg                                                        | /                                  |
|                 | Adapter                                | 12V/5A                                                           | /                                  |
| Accessories     | Adapter                                | 12V/5A                                                           | /                                  |
| Temperature     | Working temperature                    | -10~ 60°C                                                        | /                                  |
|                 | Storage temperature                    | -20 ~ 70°C                                                       | /                                  |
| Mounting        | VESA Mount                             | (VESA Wall Mount)                                                | (Swing Arm Mount/Ceiling Mount)    |
|                 | Panel Mount                            | (Front Snap-in Panel Mount)                                      | (Rear Flush Panel Mount)           |
|                 | Stand Mount                            | Desktop Stand Mount                                              | /                                  |
| Packaging       | Net weight                             | 1.83kg                                                           | /                                  |
|                 | Gross weight                           | 2.66kg                                                           | /                                  |
|                 | Product dimensions                     | 388*250*36mm (L*W*H)                                             | /                                  |
|                 | Single Unit Package Dimension          | 525*142*392mm (L*W*H)                                            | /                                  |
|                 | Carton Dimension                       | 720*540*420 (L*W*H) (Ctn Qty:5 pcs)                              | /                                  |
| Other functions | Camera                                 | 2 megapixels                                                     | 5 megapixels/8 megapixels          |
|                 | NFC                                    | NO                                                               | Customizable                       |
|                 | RFID                                   | NO                                                               | Customizable                       |
|                 | POE                                    | NO                                                               | Customizable                       |
| OEM             | Appearance, Interface, CPU, Logo, etc. |                                                                  |                                    |

The specifications provided in this document represent the standard configuration. For customized solutions or more detailed technical information, please do not hesitate to contact us.