



Shenzhen Bvsion Technology Co., Ltd.


Tel: 0086 755 23059953 Mobile: 0086-13924666965 / 00852-9373 7704 WhatsApp: +852 93737704

E-Mail: bvs.gina@lcdbvs.com Website: http://www.lcdbvs.com / http://www.bvsipc.com

Office Address: 5F, Building 9, Huafeng Science Park, Fengtang Avenue, Tangwei Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China, 518102.

Specification document

Model NO.	BVS-VR215	Standard	21.5", RK3576, 4+64GB, Android.
Brand name	BVS\OEM		
Product Type	Android Tablet PC		
Date	2026/7/20		



		Standard	optional
System	CPU	Rockchip RK3576	RK3288/RK3399/RK3566/RK3568/RK3588
	Frequency	UP to 2.2GHz	/
	GPU	Mali-G52 MC3	/
	NPU	6.0 TOPS	/
	RAM	4GB	8GB
	SSD	64GB	128GB
	Operating system	Android 14	/
Display	Screen	21.5-inch touch screen display	21.5-inch non-touch display
	Resolution	1920*1080	/
	Viewing angle	89/89/89/89 (Typ.)(CR≥10)	/
	Contrast ratio	800: 1	/
	Brightness	250 cd/m ² (Typ.)	500 cd/m ² (Typ.)
	Screen scale	16:09	/
Network	Wi-Fi	2.4G+5G-Wi-Fi, supporting Wi-Fi 802.11b/g/n protocols	/
	Ethernet	Gigabit network port	/
	BT	Bluetooth 5.2	/
	4G LTE	NO	Customizable
Interfaces	USB	3	/
	COM	/	RS232/RS485
	HD	/	/
	TF card slot	1	/
	LAN	1	/
	SIM-4G	/	1
Multi-Media	DC-IN	1	/
	Video	MPEG-1,MPEG-2,MPEG-4,H.263,H.264,VC1,RV etc.,support up to 1080	/
	Audio	MP3/WMA/AAC etc.	/
Accessories	Picture	jpeg, jpg	/
	Adapter	12V/5A	/
Temperature	Working temperature	-10~ 60°C	/
	Storage temperature	-20 ~ 70°C	/
Mounting	VESA Mount	(VESA Wall Mount)	(Swing Arm Mount/Ceiling Mount)
	Panel Mount	(Front Snap-in Panel Mount)	(Rear Flush Panel Mount)
	Stand Mount	Desktop Stand Mount	/
Packaging	Net weight	4.56kg	/
	Gross weight	5.84kg	/
	Product dimensions	532*333*40mm (L*W*H)	/
	Single Unit Package Dimension	595*431*115mm (L*W*H)	/
Other functions	Carton Dimension	666*515*610 (L*W*H) (Ctn Qty:5 pcs)	/
	Camera	2 megapixels	5 megapixels/8 megapixels
	NFC	NO	Customizable
	RFID	NO	Customizable
OEM	POE	NO	Customizable
	Appearance, Interface, CPU, Logo, etc.		

The specifications provided in this document represent the standard configuration. For customized solutions or more detailed technical information, please do not hesitate to contact us.