



Shenzhen Bvsion Technology Co., Ltd.

Tel: 0086 755 23059953 Mobile: 0086-13924666965 / 00852-9373 7704 WhatsApp: +852 93737704

E-Mail: bvs.gina@icdbvs.com Website: <http://www.icdbvs.com> / <http://www.bvsipc.com>

Office Address: 5F, Building 9, Huaifeng Science Park, Fengtang Avenue, Tangwei Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China, 518102.

Specification document

Model NO.	BVS-XC156-R-RK3288	Standard	15.6", Rockchip RK3288, 2+32GB, Android 7.1/9.1
Brand name	BVS/OEM		
Product Type	Android Tablet PC		
Date	2026/8/4		



		Standard	optional
System	CPU	Rockchip RK3288 Quad Cortex-A17 + Quad GPU Mali-T764	/
	Frequency	1.8 GHz	/
	GPU	Mali-T764	/
	DDR	4GB	4GB
	EMMC	32GB	8GB / 32GB
	Operating system	Android 7.1 / 9.1	/
Display	Screen	15.6 inch Industrial LCD Screen	/
	Resolution	1920 (RGB) × 1080, WXGA	/
	Viewing angle	89/89/89/89 (Typ.) (CR≥10)	/
	Contrast ratio	800:1 (Typ.) (Transmissive)	/
	Brightness	250 cd/m² (Typ.)	500 cd/m²
	Screen scale	16:9	/
Network	Wi-Fi	2.4G Wi-Fi, 802.11b/g/n	5G Wi-Fi
	Ethernet	1 x Gigabit Ethernet (RJ45)	/
	BT	Bluetooth V2.1+EDR / 3.0 / 3.0+HS / 4.0	/
			/
Interfaces	USB	USB 2.0 * 2, USB 3.0 * 1	/
	COM	/	TTL / RS232 / RS485 * 2 (support external NFC, Printer, Scanner, etc.)
	TF card slot	Max support 32GB TF card	/
	LAN	1	/
	DC-IN	1	/
Multi-Media	Video	H.264, H.265, H.263, MPEG4 1080P multi-video decoding, You	/
	Audio	MP3, WMA, WAV, APE, FLAC, AAC, OGG, M4A, 3GPP	/
	Picture	JPG, BMP, PNG formats browsing, rotation, slide show, zoom	/
Accessories	Adapter	DC 12V / 5A	/
Temperature	Working temperature	-20°C ~ 60°C	/
	Storage temperature	/	/
Mounting	VESA Mount	/	Customizable
	Panel Mount	/	Customizable
	Stand Mount	/	Customizable
Packaging	Net weight	2.55kg	/
	Gross weight	3.8kg	/
	Product dimensions	235*386*45mm (L*W*H)	/
	Single Unit Package Dimensions	420*480*130mm (L*W*H)	/
	Carton Dimension	520*410*470mm (L*W*H) (Ctn Qty:5 pcs)	/
Other functions	Camera	2MP	(1.3MP 720P, 2MP 1080P, 5MP)
	NFC	/	(ISO/IEC14443A)
	POE	/	Support POE power supply
OEM	Appearance, Interface, CPU, Logo, etc.		

The specifications provided in this document represent the standard configuration. For customized solutions or more detailed technical information, please do not hesitate to contact us.



Shenzhen BvSION Technology Co., Ltd.

Tel: 0086 755 23059953 Mobile: 0086-13924666965 / 00852-9373 7704 WhatsApp: +852 93737704

E-Mail: bvs.gina@icdbvs.com Website: <http://www.icdbvs.com> / <http://www.bvsipc.com>

Office Address: 5F, Building 9, Huaifeng Science Park, Fengtang Avenue, Tangwei Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China, 518102.

Specification document

Model NO.	BVS-XC156-R-RK3399	Standard	15.6", Rockchip RK3399, 2+32GB, Android 7.1 / 9.0.
Brand name	BVS/OEM		
Product Type	Android Tablet PC		
Date	2026/8/4		



		Standard	optional
System	CPU	Rockchip RK3399 Dual Cortex-A72 + Quad Cortex-A53	/
	Frequency	2.0 GHz	/
	DDR	Mali-T860 MP4	/
	EMMC	2GB	4GB
	SSD	32GB	16GB / 64GB
	Operating system	Android 7.1 / 9.1	/
Display	Screen	15.6 inch Industrial LCD Screen	/
	Resolution	1920 (RGB) × 1080, WXGA	/
	Viewing angle	89/89/89/89 (Typ.) (CR≥10)	/
	Contrast ratio	800:1 (Typ.) (Transmissive)	/
	Brightness	250 cd/m ² (Typ.)	500 cd/m ²
	Screen scale	16:9	/
Network	Wi-Fi	2.4G Wi-Fi, 802.11b/g/n	/
	Ethernet	1 x Gigabit Ethernet (RJ45)	/
	BT	Bluetooth V2.1+EDR / 3.0 / 3.0+HS / 4.1 / BLE	/
	4G LTE	/	LTE-TDD / LTE-FDD / TD-SCDMA / EDGE / GPRS / GSM (Optional)
Interfaces	USB	USB 2.0 * 2, USB 3.0 * 1	/
	COM	/	TTL / RS232 / RS485 * 2 (support external NFC, Printer, Scanner, etc.)
	TF card slot	Max support 32GB TF card	/
	LAN	1	/
	DC-IN	1	/
Multi-Media	Video	H.264, H.265, WMV, AVS, H.263, MPEG4 1080P multi-video decoding, You	/
	Audio	1 x Speaker output (2*3W), 1 x Headset output, 1 x Microphone input	/
	Picture	JPG, BMP, PNG formats browsing, rotation, slide show, zoom	/
Accessories	Adapter	DC 12V / 5A	/
Temperature	Working temperature	-20°C ~ 60°C	/
	Storage temperature	/	/
Mounting	VESA Mount	/	Customizable
	Panel Mount	/	Customizable
	Stand Mount	/	Customizable
Packaging	Net weight	2.55kg	/
	Gross weight	3.8kg	/
	Product dimensions	235*386*45mm (L*W*H)	/
	Single Unit Package Dimension	420*480*130mm (L*W*H)	/
Other functions	Camera	2MP	(1.3MP 720P, 2MP 1080P, 5MP)
	NFC	/	(ISO/IEC14443A)
	POE	/	Support POE power supply
OEM	Appearance, Interface, CPU, Logo, etc.		

The specifications provided in this document represent the standard configuration. For customized solutions or more detailed technical information, please do not hesitate to contact us.



Shenzhen BvSION Technology Co., Ltd.

Tel: 0086 755 23059953 Mobile: 0086-13924666965 / 00852-9373 7704 WhatsApp: +852 93737704

E-Mail: bvs.gina@icdbvs.com Website: <http://www.icdbvs.com> / <http://www.bvsipc.com>

Office Address: 5F, Building 9, Huaifeng Science Park, Fengtang Avenue, Tangwei Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China, 518102.

Specification document

Model NO.	BVS-XC156-R-RK3566	Standard	15.6", Rockchip RK3566, 2+32GB, Android 11
Brand name	BVS/OEM		
Product Type	Android Tablet PC		
Date	2026/8/4		



		Standard	optional
System	CPU	Rockchip RK3566 Quad-core Cortex-A55	/
	Frequency	2.0 GHz	/
	GPU	Quad-core GPU	/
	NPU	1TOPS NPU	/
	DDR	2GB	4GB
	EMMC	32GB	16GB
	Operating system	Android 11	/
Display	Screen	15.6 inch Industrial LCD Screen	/
	Resolution	1920 (RGB) × 1080, WXGA	/
	Viewing angle	89/89/89/89 (Typ.) (CR≥10)	/
	Contrast ratio	800:1 (Typ.) (Transmissive)	/
	Brightness	250 cd/m² (Typ.)	500 cd/m²
	Screen scale	16:9	/
Network	Wi-Fi	2.4G Wi-Fi, 802.11b/g/n	5G Wi-Fi
	Ethernet	1 x Gigabit Ethernet (RJ45)	/
	BT	Bluetooth	/
Interfaces	USB	USB Host * 3	/
	COM	/	TTL / RS232 / RS485 * 2 (support external NFC, Printer, Scanner, etc.)
	TF card slot	Max support 32GB TF card	/
	LAN	1	/
	SIM-4G	1	/
	DC-IN	1	/
Multi-Media	Video	H.264, H.265, AVS, H.263, MPEG4 1080P multi-video decoding, You	/
	Audio	MP3, WMA, WAV, APE, FLAC, AAC, OGG, M4A, 3GPP	/
	Picture	JPG, BMP, PNG formats browsing, rotation, slide show, zoom	/
Accessories	Adapter	DC 12V / 5A	/
Temperature	Working temperature	-20°C ~ 60°C	/
	Storage temperature	/	/
Mounting	VESA Mount	/	Customizable
	Panel Mount	/	Customizable
	Stand Mount	/	Customizable
Packaging	Net weight	2.55kg	/
	Gross weight	3.8kg	/
	Product dimensions	235*386*45mm (L*W*H)	/
	Single Unit Package Dimension	420*480*130mm (L*W*H)	/
	Carton Dimension	520*410*470mm (L*W*H) (Ctn Qty:5 pcs)	/
Other functions	Camera	2MP	(1.3MP 720P, 2MP 1080P, 5MP)
	NFC	/	(ISO/IEC14443A)
	RFID	/	/
	POE	/	Support POE power supply
OEM	Appearance, Interface, CPU, Logo, etc.		

The specifications provided in this document represent the standard configuration. For customized solutions or more detailed technical information, please do not hesitate to contact us.



Shenzhen Bvsion Technology Co., Ltd.


Tel: 0086 755 23059953 Mobile: 0086-13924666965 / 00852-9373 7704 WhatsApp: +852 93737704

E-Mail: bvs.gina@icdbvs.com Website: <http://www.icdbvs.com> / <http://www.bvsipc.com>

Office Address: 5F, Building 9, Huaifeng Science Park, Fengtang Avenue, Tangwei Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China, 518102.

Specification document

Model NO.	BVS-XC156-R-RK3576	Standard	15.6", Rockchip RK3576, 2+32GB, Android 14.
Brand name	BVS/OEM		
Product Type	Android Tablet PC		
Date	2026/8/4		



		Standard	optional
System	CPU	Rockchip RK3576 Quad Cortex-A53 + Quad Cortex-A72	/
	Frequency	2.2 GHz	/
	GPU	Mali-G52 MC3	/
	NPU	6TOPS NPU	/
	DDR	4GB	8GB
	EMMC	16GB	32GB / 64GB / 128GB
	Operating system	Android 14	/
Display	Screen	15.6 inch Industrial LCD Screen	/
	Resolution	1920 (RGB) × 1080, WXGA	/
	Viewing angle	89/89/89/89 (Typ.) (CR≥10)	/
	Contrast ratio	800:1 (Typ.) (Transmissive)	/
	Brightness	250 cd/m² (Typ.)	500 cd/m²
	Screen scale	16:9	/
Network	Wi-Fi	2.4G Wi-Fi, 802.11b/g/n	/
	Ethernet	1 x Gigabit Ethernet (RJ45)	/
	BT	Bluetooth	/
Interfaces	USB	USB Host * 3	/
	COM	/	TTL / RS232 / RS485 * 2 (support external NFC, Printer, Scanner, etc.)
	TF card slot	Max support 32GB TF card	/
	LAN	1	/
	DC-IN	1	/
Multi-Media	Video	H.265, H.264, WMV, AVS, H.263, MPEG4 1080P multi-video decoding, You	/
	Audio	MP3, WMA, WAV, APE, FLAC, AAC, OGG, M4A, 3GPP	/
	Picture	JPG, BMP, PNG formats browsing, rotation, slide show, zoom	/
Accessories	Adapter	DC 12V / 3A	/
Temperature	Working temperature	-20°C ~ 60°C	/
	Storage temperature	/	/
Mounting	VESA Mount	/	Customizable
	Panel Mount	/	Customizable
	Stand Mount	/	Customizable
Packaging	Net weight	2.55kg	/
	Gross weight	3.8kg	/
	Product dimensions	235*386*45mm (L*W*H)	/
	Single Unit Package Dimension	420*480*130mm (L*W*H)	/
	Carton Dimension	520*410*470mm (L*W*H) (Ctn Qty:5 pcs)	/
Other functions	Camera	2MP	(1.3MP 720P, 2MP 1080P, 5MP)
	NFC	/	(ISO/IEC14443A)
	POE	/	Support POE power supply
OEM	Appearance, Interface, CPU, Logo, etc.		

The specifications provided in this document represent the standard configuration. For customized solutions or more detailed technical information, please do not hesitate to contact us.



E-Mail: bvs.gina@lcdbvs.com Website: <http://www.lcdbvs.com> / <http://www.bvsipe.com>

Office Address: 5F, Building 9, Huafeng Science Park, Fengtang Avenue, Tangwei Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China, 518102.

Specification document

Model NO.	BVS-XC156-R-RK3588	Standard	15.6", Rockchip RK3588, 8+128GB, Android 12.
Brand name	BVS/OCM		
Product Type	Android Tablet PC		
Date	2026/8/4		



		Standard	optional
System	CPU	Rockchip RK3588	/
	Frequency	Up to 2.4GHz Octa-core	/
	GPU	Mali-G610 MP4	/
	NPU	Support 6T	/
	DDR	8GB	(2GB / 4GB / 8GB)
	EMMC	128GB	(32G/ 64G /128G)
	Operating system	Android 12	/
Display	Screen	15.6 inch Industrial LCD Screen	/
	Resolution	1920 (RGB) × 1080, WXGA	/
	Viewing angle	89/89/89/89 (Typ.) (CR≥10)	/
	Contrast ratio	800:1 (Typ.) (Transmissive)	/
	Brightness	250 cd/m² (Typ.)	500 cd/m²
	Screen scale	16:9	/
Network	Wi-Fi	2.4G Wi-Fi, 802.11b/g/n	/
	Ethernet	1 x Gigabit Ethernet (RJ45)	/
	BT	Bluetooth	/
Interfaces	USB	USB Host * 3	/
	COM	/	TTL / RS232 / RS485 * 2 (support external NFC, Printer, Scanner, etc.)
	TF card slot	Max support 32GB TF card	/
	LAN	1	/
	DC-IN	1	/
Multi-Media	Video	H.265, H.264, WMV, AVS, H.263, MPEG4 1080P multi-video decoding, YouView	/
	Audio	MP3, WMA, WAV, APE, FLAC, AAC, OGG, M4A, 3GPP	/
	Picture	JPG, BMP, PNG formats browsing, rotation, slide show, zoom	/
Accessories	Adapter	DC 12V / 3A	/
Temperature	Working temperature	-20°C ~ 60°C	/
	Storage temperature	/	/
Mounting	VESA Mount	/	Customizable
	Panel Mount	/	Customizable
	Stand Mount	/	Customizable
Packaging	Net weight	2.55kg	/
	Gross weight	3.8kg	/
	Product dimensions	235*386*45mm (L*W*H)	/
	Single Unit Package Dimension	420*480*130mm (L*W*H)	/
	Carton Dimension	520*410*470mm (L*W*H) (Ctn Qty:5 pcs)	/
Other functions	Camera	2MP	(1.3MP 720P, 2MP 1080P, 5MP)
	NFC	/	(ISO/IEC14443A)
	POE	/	Support POE power supply
OEM	Appearance, Interface, CPU, Logo, etc.		

The specifications provided in this document represent the standard configuration. For customized solutions or more detailed technical information, please do not hesitate to contact us.