



Shenzhen Bvsion Technology Co., Ltd.

Tel: 0086 755 23059953 Mobile: 0086-13924666965 / 00852-9373 7704 WhatsApp: +852 93737704

E-Mail: bvs.gina@lcdbvs.com Website: <http://www.lcdbvs.com> / <http://www.bvsipc.com>

Office Address: 5F, Building 9, Huafeng Science Park, Fengtang Avenue, Tangwei Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China, 518102.

Specification document

Model NO.	BVS-ZR215-RK3576	Standard	21.5", Rockchip RK3576, 4+64GB, Android 14.
Brand name	BVS\OEM		
Product Type	Android Tablet PC		
Date	2026/8/5		



		Standard	optional
System	CPU	Rockchip RK3576 Quad Cortex-A53 + Quad Cortex-A72	/
	Frequency	2.2 GHz	/
	GPU	Mali-G52 MC3	/
	NPU	6TOPS NPU	/
	DDR	4GB	8GB
	EMMC	64GB	16GB / 32GB / 128GB
	Operating system	Android 14	/
Display	Screen	21.5 inch Industrial LCD Screen	/
	Resolution	1920(RGB) × 1080 , WXGA	/
	Viewing angle	89/89/89/89 (Typ.) (CR≥10)	/
	Contrast ratio	3000:1 (Typ.) (Transmissive)	/
	Brightness	250 cd/m ² (Typ.)	500 cd/m ²
	Screen scale	16:9	/
Network	Wi-Fi	2.4G Wi-Fi, 802.11b/g/n	/
	Ethernet	1 x Gigabit Ethernet (RJ45)	/
	BT	Bluetooth	/
	4G LTE	/	/
Interfaces	USB	USB Host * 3	/
	COM	/	TTL / RS232 / RS485 * 2 (support external NFC, Printer, Scanner, etc.)
	HD	/	/
	TF card slot	Max support 32GB TF card	/
	LAN	1	/
	SIM-4G	/	/
	DC-IN	1	/
Multi-Media	Video	P8, MAV, WMV, AVS, H.263, MPEG4 1080P multi-video decoding, YouTube	/
	Audio	MP3, WMA, WAV, APE, FLAC, AAC, OGG, M4A, 3GPP	/
	Picture	JPG, BMP, PNG formats browsing, rotation, slide show, zoom	/
Accessories	Adapter	DC 12V / 5A	/
Temperature	Working temperature	-20°C ~ 60°C	/
	Storage temperature	/	/
Mounting	VESA Mount	/	Customizable
	Panel Mount	/	Customizable
	Stand Mount	/	Customizable
Packaging	Net weight	5.15kg	/
	Gross weight	6.28kg	/
	Product dimensions	330*581*55mm (L*W*H)	/
	Single Unit Package Dimension	595*431*115mm (L*W*H)	/
	Carton Dimension	610*600*450 (L*W*H) (Ctn Qty:5 pcs)	/
Other functions	Camera	2MP	(1.3MP 720P, 2MP 1080P, 5MP)
	NFC	/	(ISO/IEC14443A)
	RFID	/	/
	POE	/	Support POE power supply
OEM	Appearance, Interface, CPU, Logo, etc.		

The specifications provided in this document represent the standard configuration. For customized solutions or more detailed technical information, please do not hesitate to contact us.